

PRODUCT SPECIFICATION

PRODUCT DESCRIPTION	CLEAR SUREWRAPMAX MEGA 500MM X 300M 20UM POLYETHYLENE STRETCH FILM
PRODUCT CODE	PSW20HMAX

SPECIFICATION

FILM DIMENSIONS	UNITS	SPECIFICATION	TESTING METHOD
THICKNESS	MICRONS	20um ±2um	THICKNESS GAUGE
WIDTH	MM	500mm ±5mm	MEASURING TAPE
LENGTH	METRES	300m ±5m	HIGH SPEED EMCODER
DENSITY	G/CM ³	0.91-0.92	ASTM D-1505

FILM PROPERTIES		UNITS	SPECIFICATION	TESTING METHOD
TENSILE STRENGTH	MD	MPA	≥ 29.2	ASTM D 882
	TD		≥ 14.9	
BREAK ELONGATION	MD	%	≥ 328.5	
	TD		≥ 630	
DART DROP		G	≥ 50.4	ASTM D 1709
PUNCTURE		N	≥ 20.88	FPT-750
ULTIMATE FILM BREAK		%	≥ 171	

CONDITION OF TESTING
Temperature 23+/-2 °C Relative Humidity 55+/- 5%



We hereby certify that the product delivered to you has been tested and conforms to the following specification.

The above mentioned data refer to standard tests carried out in a laboratory. They are to be considered as merely indicative, in order to simplify the choice and use of the relevant field of application, and are not given for guaranteed purposes.

We reserve the right to modify these data if necessary, without prior notice.

Our products validity period is 1 year from production date.